Model No. VS12843

VX2739wm

69cm/ 27" Viewable Widescreen LCD

The Biggest Impact to Your Viewing Experience

- **World Wide first 1ms 27" LCD**
- **Full HD 1080p performance for unsurpassed HD viewing**
- **High brightness and 100,000 DCR reflect true colour**
  300 nits high brightness delivers precise accurate colour to realistically display a full array of brilliant shades and hues.
- **Multiple inputs including HDMI/DVI input with HDCP give you extensive connectivity options for high-definition data and entertainment**
- **Impressive 100,000:1 dynamic contrast ratio provides greater detail and definition**
  Provides darker levels of black and better overall front-of-screen performance.
- **SRS Premium Sound**
  The two watt built-in audio speakers provide superior audio quality for all multimedia applications while reducing desktop space required by separate speakers.
- **Eco-mode**
  Automatically reduces power consumption and can extend back-light life and reduce operating power consumption by up to 40%
- **Windows® 7 certified**

Model Name		VX2739wm
LCD	Size	69cm/ 27" wide Colour TFT Active Matrix LCD 16:9 aspect ratio
	Optimum Resolution	1920×1080
	Brightness (cd/m²)	300 (typical)
	Contrast Ratio (typical)	1200:1
	Dynamic Contrast Ratio	100,000:1
	Viewing Angle (CR≧10)	170° (H), 160° (V)
	Response Time (ms)	3.4ms (typical) / 1ms (G to G)
	Panel Surface	Anti-Glare, Hard coating(3H)
	Light Source (Hours)	50,000 hrs (minimum)
	Colour Support (Million of colours)	16.7 Million
INPUT	Analogue	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p)
	Sync	Separate
	Frequency (Fh / Fv)	24–83kHz / 50–76Hz
COMPATIBILITY	PC	VGA up to 1920×1080 Non Interlaced
	Mac	1920×1080 Non Interlaced
CONNECTOR	Analogue	1×15 pin mini D-sub
	Digital	1×DVI-D, HDMI (Supported HDMI 1.3 spec)
	power	Built-in power Adapter, 3-Pin plug
	Audio	Audio Out - 3.5 mm jack (blue) / Audio In - 3.5 mm jack (green)
	USB V2.0	Up stream ×1, Down stream ×4
SPEAKER	Speaker	2W×2 (SRS Premium sound)
POWER	Voltage	AC 100-240V (Universal); 50/60Hz (Switch)
	Consumption (W)	51 W (typical) w/o Audio , w/o USB 62 W (typical) w/o Audio 58 W (typical) w/o USB 71 W (maximum; full)
	Save mode (W)	≦1W
ERGONOMICS	Tilt	20~-5 degrees
CONTROLS	Basic	[1], [2], Power, Down[▼], Up[▲]
	OnView / OSD	Auto Image Adjust, Contrast / Brightness, Input Select, D-SUB, DVI, HDMI PC, HDMI AV, Audio Adjust, Volume, mute, Color Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B], Information Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Display Mode, ECO Mode Setup Menu, Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off, Sleep
OPERATING CONDITIONS	Temperature	0 - 40 (°C) / 32 - 104 (°F)
	Humidity (Non condensed)	20 - 90 (%)
DIMENSIONS (WxHxD)	Physical (w/ stand)	647x490x250 (mm)
WEIGHT	Net (w/ stand)	7.2 kg /15.84 lb
REGULATIONS		UL, CUL, FCC-B (ICES), CB, CE, CES-003B, Nemko ERGO (MPR II, ISO 13406-2), TUV-S, NOM, GOST-R, HYGIENIC, CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS, Ukraine
WALL MOUNT (mm)	VESA® Mount Compliant	200mm × 100mm

For more product information, visit us at www.viewsoniceurope.com
VSE 2011/01/26 V6

ViewSonic® See the difference™